



Maintenance Guide

- Avoid using wash/shampoo during first 7 days - use only clear water to wash your RV during this period if required.
- Wash your RV as required using a PH neutral wash/shampoo. It is recommended to use a product from the Vantec RV Care range.
- Wash your RV in a cool, shady area, and in warmer climates, allow the metal of your RV to cool prior to washing. A hot surface causes the washing agents to evaporate quickly, leading to water spotting.
- Hose your RV prior to washing to dislodge and loosen dirt, dust or mud.
- Use a good quality clean sponge then flush the surface thoroughly with clean water. As dirt and contaminants can become trapped in the sponge (which can lead to scratches and swirl marks on the paint surface), rinse the sponge with clean water regularly. For the best result, dry your RV with a good quality chamois or drying towel.
- Do not use any polishes on your RV which can be abrasive, or any washing agents that contain degreasers or solvents. Use of these products may reduce the life of the coating.
- Remove environmental contaminants (e.g. bird droppings, bug splatter and tree sap) as soon as possible in order to neutralise the acid effects of these contaminants. Apply Vantec RV Care or PH neutral RV wash/shampoo directly to the affected area, allow the contaminants to soften, then wash as per instructions above. Do not use anything abrasive (e.g. scours, brushes or fingernails) to remove such contaminants.
- If your RV is repaired or replaced, the product must be reapplied. Call Vantec RV Care to discuss any reapplication queries or to arrange reapplication.